# Talken Color Srl A0352 - SUPERATTIVO SPRAY

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 1 / 10

(Mi)

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **A0352** 

Product name SUPERATTIVO SPRAY

Chemical name and synonym FORMULA PROTETTIVA E LUCIDANTE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use PULITORE LUCIDANTE PER MARMI E BRONZI IN AEROSOL.

1.3. Details of the supplier of the safety data sheet

Name Talken Color Srl
Full address via Don Milani 15
District and Country 20025 Legnano

Italia
Tel. 0331/579100
Fax 0331/579372

e-mail address of the competent person

responsible for the Safety Data Sheet tecnico@talkencolor.it

1.4. Emergency telephone number

For urgent inquiries refer to CENTRO ANTIVELENI dl Milano-Niquarda Tel 0266101029

#### **SECTION 2. Hazards identification**

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
Eye irritation, category 2 H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure, category

H336

May cause drowsiness or dizziness.

3

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

**H222** Extremely flammable aerosol.

**H229** Pressurised container: may burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

Precautionary statements:

P102 Keep out of reach of children.

# Talken Color Srl A0352 - SUPERATTIVO SPRAY

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 2 / 10

#### SECTION 2. Hazards identification .../>>

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**P211** Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.

**P501** Dispose of contents in different containers for steel

Contains: PROPAN-2-OL

NAPHTHA (PETROL.) HYDROTREATED HEAVY

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients**

#### 3.1. Substances

Information not relevant

#### 3.2. Mixtures

#### Contains:

Identification Conc. % Classification 1272/2008 (CLP)

PROPAN-2-OL

CAS 67-63-0 38 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336

EC 200-661-7 INDEX 603-117-00-0 Reg. no. 01-2119457558-25

NAPHTHA (PETROL.) HYDROTREATED HEAVY

CAS 64742-48-9 9,7 Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Note P

EC 265-150-3 INDEX 649-327-00-6

Reg. no. 01-2119463258-33-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants. Percentage of propellants: 49,50 %

# **SECTION 4. First aid measures**

# 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

# 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# Talken Color Srl A0352 - SUPERATTIVO SPRAY

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 3 / 10

# **SECTION 5. Firefighting measures**

### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

#### 5.3. Advice for firefighters

**GENERAL INFORMATION** 

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

#### 6.2. Environmental precautions

Do not disperse in the environment.

# 6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

## 7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

# 7.3. Specific end use(s)

Information not available

# Talken Color Srl A0352 - SUPERATTIVO SPRAY

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 4 / 10

# **SECTION 8. Exposure controls/personal protection**

# 8.1. Control parameters

Regulatory References:

ESP España INSHT - Límites de exposición profesional para agentes químicos en España 2015

GBR United Kingdom EH40/2005 Workplace exposure limits

TLV-ACGIH ACGIH 2016

PROPAN-2-OL								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15r	nin			
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP	500	200	1000	400			
WEL	GBR	999	400	1250	500			
TLV-ACGIH		492	200	983	400			

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

TLV of solvent mixture: 492 mg/m3

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYÉ PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance aerosol Colour milky

Odour characteristic of solvent

Odour threshold Not available pH Not available Melting point / freezing point Not available Initial boiling point Not applicable Boiling range Not available Flash point Not applicable Evaporation Rate Not available

Flammability of solids and gases non applicabile per aerosol

Lower inflammability limit Not available
Upper inflammability limit Not available
Lower explosive limit Not available
Upper explosive limit Not available

# Talken Color Srl A0352 - SUPERATTIVO SPRAY

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 5 / 10

### SECTION 9. Physical and chemical properties ..../>>

Vapour pressure Not available Vapour density Not available

Relative density 0,74

Solubility soluble in organic solvents

Partition coefficient: n-octanol/water Not available
Auto-ignition temperature Not available
Decomposition temperature Not available
Viscosity Not available

Explosive properties durante l'uso puo' formare con l'aria miscele esplosive o infiammabili

Oxidising properties not applicable

9.2. Other information

Total solids (250°C / 482°F) 2,80 %

VOC (Directive 2010/75/EC): 97,20 % - 718,31 g/litre

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

Avoid overheating.

# 10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

### 10.6. Hazardous decomposition products

Information not available

## **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

## 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

# Talken Color Srl A0352 - SUPERATTIVO SPRAY

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 6 / 10

#### SECTION 11. Toxicological information .../>>

LC50 (Inhalation) of the mixture: LD50 (Oral) of the mixture: LD50 (Dermal) of the mixture: Not classified (no significant component) Not classified (no significant component) Not classified (no significant component)

PROPAN-2-OL

 LD50 (Oral)
 4710 mg/kg Rat

 LD50 (Dermal)
 12800 mg/kg Rat

 LC50 (Inhalation)
 72,6 mg/l/4h Rat

NAPHTHA (PETROL.) HYDROTREATED HEAVY

LD50 (Oral) > 5000 mg/kg Rat LD50 (Dermal) > 2000 mg/kg Rabbit

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

#### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

# REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

# **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

# 12.1. Toxicity

NAPHTHA (PETROL.) HYDROTREATED HEAVY

LC50 - for Fish 8,2 mg/l/96h Pimephales promelas EC50 - for Crustacea 4,5 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 3,1 mg/l/72h Pseudokirchnerella subcapitata

### 12.2. Persistence and degradability

@EPY 9.4.5 - SDS 1004.4

# Talken Color Srl A0352 - SUPERATTIVO SPRAY

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 7 / 10

# SECTION 12. Ecological information .../>>

PROPAN-2-OL Rapidly degradable

NAPHTHA (PETROL.) HYDROTREATED HEAVY Rapidly degradable

rapian, angranam

#### 12.3. Bioaccumulative potential

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

#### 12.4. Mobility in soil

NAPHTHA (PETROL.) HYDROTREATED HEAVY
Partition coefficient: soil/water 1,78

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

## 14.1. UN number

ADR / RID, IMDG, IATA: 1950

## 14.2. UN proper shipping name

ADR / RID: AEROSOLS IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

# 14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



### 14.4. Packing group

ADR / RID, IMDG, IATA:

# Talken Color Srl **A0352 - SUPERATTIVO SPRAY**

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 8 / 10

#### SECTION 14. Transport information .../>>

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA:

14.6. Special precautions for user

ADR / RID: HIN - Kemler: --Limited Quantities: 1 L Tunnel restriction code: (D)

Special Provision: -

IMDG: EMS: F-D, S-U Limited Quantities: 1 L

Maximum quantity: 100 Kg IATA: Cargo: Packaging instructions: 130 Packaging instructions: 130

Pass.: Maximum quantity: 25 Kg

Special Instructions: A802

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

# **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH)

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

Substances subject to the Rotterdam Convention:

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

# 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Aerosol 1 Aerosol, category 1 Aerosol 3 Aerosol, category 3

Flam. Liq. 2 Flammable liquid, category 2 Flam. Liq. 3 Flammable liquid, category 3 Asp. Tox. 1 Aspiration hazard, category 1 Eye Irrit. 2 Eye irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

# Talken Color Srl A0352 - SUPERATTIVO SPRAY

Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 9 / 10

#### SECTION 16. Other information .../>>

H225 Highly flammable liquid and vapour.H226 Flammable liquid and vapour.

**H304** May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

**EUH066** Repeated exposure may cause skin dryness or cracking.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### Revision nr.14 Dated 30/11/2017 Printed on 30/11/2017 Page n. 10 / 10

EN

# Talken Color Srl A0352 - SUPERATTIVO SPRAY

**SECTION 16. Other information** .../>>

Changes to previous review: The following sections were modified: 01 / 02 / 03 / 04 / 08 / 09 / 11 / 12.