



TALKEN COLOR S.R.L.
Sede e stabilimento:
20025 Legnano (Mi) - Via Don Milani, 15
Tel. 0331.579100 r.a. - Fax 0331.579372
Mecc. 9720178
Email: info@talkencolor.it
www.talkencolor.it

Reg. Imprese di Milano
Società n. 04614930156
P. Iva / C.F. 04614930156
Cod. ISO/IVA IT 04614930156
Cap. Soc. € 10.400,00 i.v.

Revisione del 02/11/2017

TECHNICAL DATA SHEET

code	A0461
Commercial name	SMALTO 2000 SPRAY
Chemical Complexion	SWIFT DRYING ALKYD PAINT
Nominal content	520 mL
Net content	400 mL

PHYSICAL- CHEMICAL SPECIFICATIONS:

PHISICAL STATE	Pigmented liquid
CHEMICAL COMPLEXION	Swift drying alkyd paint
SOLUBILITY	Soluble in acetone and/or nitro thinner.
DRYNESS	Without dust: 15 min. Sense of touch: 25 min. Deep drying: within 6 h
RESA	
RESISTANCE	This is a no-yellowing over time product. It resists over time and it is also resistant to engine oils, benzene and detergents.

PRODUCT DESCRIPTION:

Smalto 2000 is a no-yellowing alkyd resin available in matte or shiny finishing. It dries in 10 minutes and it takes 48 hours to have a glossy surface. It can be overpainted. It is resistant to benzene. This product can be used on any kind of surface: Metals, wood, glass, aluminum, hard plastics etc.

TECHNICAL SPECIFICATIONS:

High surface hardness.
Scratch and bump resistant product with a tough grip to the surface.
It can be overpainted and the first coat already gives visible high quality results.

FIELDS OF APPLICATION:

This product is suitable for any kind of object you want to renew.
HOME: furniture, domestic appliances, decorations.
INTERIOR END EXTERIOR DECORATIONS: fence, gate, plastic pots, lamps, bikes, motorbikes...
DO IT YOURSELF
DECOUPAGE
Supports: Iron, aluminum, steel, glass, plastic, wood, etc..

SUPPORT GROUNDWORK:

Sand down the support using n°400 sandpaper. Clean up the surface using petrol or alcohol. Turn the can upside and shake it for one minute approximately; then spray aloft a couple of times. These procedures are really important in order to get the real colour. Spray the paint holding the can at close range (approximately cm. 30)
Avoid leaking spraying both undercoat & topcoat.

UNTREATED METAL: we recommend you to undercoat our product "areosol rust preserver"

PLASTIC: we recommend you to undercoat our product "areosol plastic primer"

STORAGE:

Keep dry. Do not keep under direct sunshine or any other hotness.

The above technical information are given just considering our actual knowledge. Our customers are kindly required to control by themselves, in order to value final results.

Talken Color srl relieves itself from any responsibility for applications in a way that does not comply with the recommendations of use